

### TSP 030 – Finixa adhesion primer 400ml for easy seam sealer

#### **Description**

High quality, fast drying plastic primer to treat surfaces, treated and untreated, of several types of plastic.

#### **Product characteristics**

Fast drying  
Excellent adhesion  
Re-sprayable with all lacquer systems

#### **Physical and Chemical Characteristics**

Contents : 400 ml  
Base : Polyolefine resin  
Colour : Transparent  
VOC-content : Approximately 99% w/w  
Solid content : Approximately 1% w/w  
Coverage : 2 to 3 m<sup>2</sup>  
Re-sprayable : After 10 to 15 minutes

#### **Usage**

Before use, carefully read the directions on the packaging and act accordingly.

#### **Pre Treatment**

The surface should be clean, dry and free of grease. When desired, slightly sand the surface, grain 600.

#### **Treatment**

The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 15 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.

Apply the plastic primer in maximum two (2) thin layers. After drying, without sanding, re-sprayable with all lacquer systems.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds). The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

*This information corresponds to our current knowledge on the subject. It is offered solely to provide possible suggestions for our own experimentation.*

*It is not intended, however, to substitute for any testing you may need to conduct to determine for yourself the suitability of our products for your particular purposes.*

*This information may be subject to revision as new knowledge and experience becomes available.*

*Since we cannot anticipate all variations in actual end-use conditions, Chemicar make no warranties and assume no liability in connection with any use of this information.*

*This information does not constitute a specification and is only intended to show the typical properties of the product. Product safety information is available on request.*

*Data in this Technical Data Sheet relates only to the specific materials designated here in and not to use in combination with any other material or process.*

*The information given here is the best available at time of issue. It is based on our present knowledge but does not constitute a contractual description of product properties.*